



EASY4LINK E4L-HYG600-1G GPON ONU

Overview

EASY4LINK E4L-HYG600-1G is the single port GPON optical network terminal series. It provides one GE interface, one optical interface, it's very suitable for home and small business users, can satisfy the FTTH high-speed data transmission.



Model	EASY4LINK E4L-HYG600-1G
User interface	1 10/100/1000M RJ45 port.
PON	Transmission speed :upstream1.25Gbps/downstream2.5Gbps Network coverage radius: 20KM Optical receive sensitivity: ≤ -28 dBm Luminous power: > 0 dBm Security: ONU authentication mechanism
Protocol	Compliant with IEEE 802.3ah YD/T 1475-2006 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IEEE 802.1w, RSTP IEEE 802.3ad (LACP) Ethernet-II, Ethernet-SNAP
VLAN	Port-based VLAN GVRP IEEE 802.1Q VLAN

QOS	Backpressure flow control(half-duplex) IEEE 802.3x flow control(full-duplex) Prevent Head Of Line IEEE 802.1p, CoS WR,SP and FIFO queue scheduling algorithm Port rate limit
Safety	IEEE 802.1x, access control based upon Port; support local and remote RADIUS. CHAP,EAP certification; Storm control, port protection,
Management	Various management modes such as Web, TELNET Debug function.
Environment	Operating temperature:0℃~60℃; Operating humidity:10%~85% non-condensing
	Storage temperature:-40℃~80℃; Storage humidity:5%~95% non-condensing
Power supply	110~240VAC 12V/0.5A DC power interface size:1.3mm/3.5mm
Power Consumption	6W

Order Information

Model	Description
EASY4LINK E4L-HYG600-1G	GPON ONU, One 10/100/1000M RJ45 port. Color: White



