

1GE G/EPON ONU User Manual





Connection Cable:

- Please connect the single-mode fiber with SC/UPC connector to the PON Interface. Supported up to 20Km distance
- Please connect the MDI/MDI-X cross cable to the 10/100/1000 Mbps Base-T Interface.
- Please connect the 12V/0.5A power adaptor to the device and the 220V power socket.

LED Indicator:

PWR	On: Normal power supply	
PVVK	Off: power off or power supply faults	
	On: ONU has already been registered to the OLT	
LINK/ACT	Blink: ONU has connected and is	
	registering.	
	Off: there is no optical signal	
Green-LED	On: normal network interface connected	
(network port)	Off: there is no cable insert	
	On: normal network interface connected,	
Yellow-LED	but no data transmission	
(network port)	Blink: normal network communication Off: there is no cable insert	

Factory Default Configuration:

Login Username/password: admin/admin

Default IP Address: 192.168.1.1

Default Subnet Mask: 225.225.225.0

Packing list:

NO.	Name	Quantity
1	G/EPON ONU	1SET
2	AC/DC Adapter	1PC
3	User manual	1PC
4	RJ 45 Network Cable	1PC

Brief Introduction

E4L-HYG600-1G ONU is an optical network unit developed for Gigabit broadband network access. applies computer network technology and network access technology build home networking center. network devices to share interconnects family internet connection. It will offer to users with abundant. diversity, personality, convenient, safety and efficient service.

1GE G/EPON ONU

User Manual (V1.0)

